



HIGHLIGHTS



Projected Capacitive Touch Screen



USB MSR with Encryption (optional)



USB Interface



Sleek and Stylish Design

SPECIFICATIONS

DISPLAY

Display Size: 15"
Optimal Resolution: 1024 x 768
Panel Brightness: 300 cd/m2 (typical)
Contrast Ratio: 600:1

TOUCH TECHNOLOGY

Projected Capacitive Touch Screen

CHARACTERISTICS

Response Time: 8ms (typical)
Tilt Angle: 0° - 70°
Viewing Angle: 160°

INPUT

Input Video Signal: VGA & DVI
Touch Function: USB

POWER

Power Consumption: 20W operation / 3W standby
Input Frequency: Horizontal 31.5 - 60.2KHz; vertical 56.3 - 75Hz
Power Supply: DC 12V +/- 10%

EXTERNAL I/O PORTS

USB Port: 2x USB out, 1x USB in (B type)
Video: 1x VGA (D-Sub 15pin), 1x DVI-D
Controls: 4x OSD buttons, status LED, 1 power button
Speakers: 2x 2w

ENVIRONMENT

Operating Temperature: 0° F - 40° F
Storage Temperature: 10° F - 50° F
Operating Humidity: 20% - 80% RH non-condensing
Storage Humidity: 10% - 90% RH non-condensing

DIMENSIONS

Dimension: 14.4(W) x 13.3(H) x 7.9(D)
Weight: 10.3lbs (net)

OPTIONAL PERIPHERALS

Slim MSR (encryption optional)
Fingerprint reader
Augusta reader / EMV



KEY FEATURES

1	15" Projected Capacitive Touch Screen
2	Slim MSR (encryption optional)
3	Standard Speakers
4	Multiple Base Options